



12M26.3 IMO II EPA3

Auxiliary Diesel Engine





Number of cylinders	V12
Bore and stroke (mm)	150 X 150
Displacement (L)	31.8
Engine rotation	Counterclockwise
Idle speed (rpm)	650
Flywheel housing	18"
Flywheel	SAE 0

12M26.3				Fuel Consumption		Emissions
Ratings	kW	rpm	HP	g/kWh	l/h	IMO
PRP	882	1500	1199	197	207	II
PRP	1002	1800	1362	199	237	II


Generator Sets Engines

Power Class		Definition
PRP	Prime Power	Unrestricted running time Time at full load $\leq$ 500hrs/year Load variation $\leq$ 75% of rated power 10% overload 1hr/12hrs
ESP	Emergency Standby Power	Running time 200hrs/year max Load variation 110% of Prime power Average Load factor should not exceed 70% of the engine's ESP rating

Baudouin's Engine DNA: Genuine Marine Power, Efficiency & Reliability

Our genuine marine engine design is specifically engineered for marine applications, ensuring durability, performance, and seamless integration in the most demanding environments. Designed for easy maintenance, our engines feature individual cylinder heads, allowing for quick servicing and minimal downtime to ensure uninterrupted operations. Built with key components made from highly durable materials, our engines guarantee long-term reliability and endurance in every condition.

Dimensions and dry weight (mm/kg)



3350kg

Weight with 5% tolerance

*total

**from flywheel

Standard equipment

Cooling System

Two-stage cooling circuit with integrated HT thermostatic valve
High efficiency heat exchanger (Tube Type) with integrated fresh water expansion tank
Gear-driven self-priming raw water pump with bronze impeller

Lubrication System

Duplex full-flow spin-on lube oil filters
Freshwater-cooled lube oil cooler
Mechanical oil drain pump

Fuel System

Electronically controlled common-rail fuel injection system
Double-wall fuel injection pipe with leakage detection system
Duplex fuel filters, replaceable while engine is running
Electric fuel priming pump

Intake Air and Exhaust System

Fresh water cooled exhaust gas manifold
High efficiency dry-type turbocharger with heat insulation
Raw water cooled charge air cooler

Electrical System

24V DC system, Insulated
Electrical starter
Battery Charger 190A

Optional Equipment

50/60Hz frequency, 4 poles
Insulation/heating class H/H
Electronic voltage regulation

Brushless excitation
IP23 protection, marine impregnation
Double bearing

Power definition

(Standard Standard ISO 3046-1:2002)

Reference conditions

Ambient temperature	25°C / 77°F
Barometric pressure	100 kPa
Relative humidity	30%R
Raw water temperature	25°C / 77°F

Fuel oil

Relative density	0,840 ± 0,005
Lower calorific power	42 700 kJ/kg
Consumption tolerances	0 ± 5%
	(DIN ISO 3046-1)
Inlet limit temperature	35°C / 95°F

Our ratings also comply with classification societies maximum temperature definition without power derating.

Ambient temperature	45°C / 113°F
Raw water temperature	32°C / 90°F