





6M16

Marine propulsion engine



Number of cylinders	L6
Bore and stroke (mm)	126 x 130
Displacement (L)	9.7
Engine rotation	Counterclockwise
Idle speed (rpm)	650
Flywheel	14"
Flywheel housing	SAE 1

Rated power

Rating	kW	rpm	HP	Fuel consumption			IMO
				Optimum value	Rated power		
				g/kWh	g/kWh	l/h	
P1	240	2100	326	200	218	62	II
P2	264	2100	359	203	225	70	II

P1 - CONTINUOUS DUTY - Severe continuous application with little or no engine speed / load variations.

Displacement hull:

- Engine mean load factor: 100%.
- Annual duration of use: Unrestricted.
- Use under full load: unlimited (100%).

Application examples: Deep Sea vessels and shrimp trawlers, high sea or river tugboats, towboats, cargos, cargo boats, dredgers, ferries.

P2 - HEAVY DUTY - Continuous application with frequent variations in engine speed and load.

Displacement or semi-displacement hull:

- Engine mean load factor: 80%.
- Annual duration of use: 5,000 hours.
- Use under full load: 8 hours in a 12-hours period (66%).

Application examples: Annual passenger vessels, harbour tugs, self-propellers, coasters, fast fishing boats such as tuna boats, seiners, pot vessels or liners, buoying vessels, oceanographic research vessels.

P3 - INTERMITTENT DUTY - Intermittent application with significant variations in engine speed and load.

Planning or semi-planning hull:

- Engine mean load factor: 70%.
- Annual duration of use: 3,000 hours.
- Use under full load: 2 hours in a 12-hours period (16%).
- Cruising speed is less than 90% of nominal engine speed.

Application examples: Seasonal passenger vessels, fishing launches, pilot boats, pump boats, displacement sailboats, trawlers, bow thrusters.

P4 - LIGHT DUTY - Light application with significant variations in engine speed and load.

Planning hull:

- Engine mean load factor: 90%.
- Annual duration of use: less than 1,500 hours.
- Use under full load: 1 hour in a 12-hours period (8%).
- Cruising speed is less than 80% of nominal engine speed.

Application examples: Survey or rescue fast vessels, military fast vessels, patrol boats, commercial pleasure craft.

P5 - HIGH PERFORMANCE DUTY - High performance application with significant variations in engine speed and load:


- Engine mean load factor : 60%.
- Annual duration for use: 500 hours.
- Use under full load: 1 hour in a 12-hours period (8%).

Application examples: Private pleasure boats, multi-hull pleasure boats.

WARRANTY DISCLAIMER

Warranty does not apply whenever the engine operation conditions differ from the initial duty class - P1, P2, P3, P4 and P5 - operational conditions. The operator must therefore modify the duty class accordingly, to benefit from SIMB warranty coverage.

Dimensions and dry weight (mm/kg)



Standard equipment

Cooling System

Two-stage cooling circuit with integrated HT thermostatic valve
High efficiency heat exchanger (Tube Type) with integrated fresh water expansion tank
Gear-driven self-priming raw water pump with rubber impeller
Belt-driven centrifugal freshwater pump

Lubrication System

Duplex full-flow spin-on lube oil filters
Freshwater-cooled lube oil cooler
Mechanical oil drain pump

Fuel System

Mechanical fuel injection system
Double-wall fuel injection pipe with leakage detection system
Duplex fuel filters, replaceable while engine is running
Simplex fuel prefilter with water separator
Mechanical fuel priming pump

Intake Air and Exhaust System

Dry exhaust manifold
High efficiency dry-type turbocharger with heat insulation
Low water temperature cooled intake air cooler

Electrical System


24V DC system, Insulated
Electrical Starter
Battery Charger 55A

Optional Equipment


Keel Cooling configuration
Front PTO
Wet exhaust
Elastic pads

Performance

P1 - 240 kW - 2100 rpm



P2 - 264 kW - 2100 rpm



Power definition

(Standard ISO 3046-1:2002)

Reference conditions

Ambient temperature	25°C / 77°F
Barometric pressure	100 kPa
Relative humidity	30%R
Raw water temperature	25°C / 77°F

Fuel oil

Relative density	0,840 ± 0,005
Lower calorific power	42 700 kJ/kg
Consumption tolerances	+ 5%
	(DIN ISO 3046-1)
Inlet limit temperature	35°C / 95°F

Our ratings also comply with classification societies maximum temperature definition without power derating.

Ambient temperature	45°C / 113°F
Raw water temperature	32°C / 90°F